

LiveLED 12

Small Size. 230 Lumen RGB Output.



Description

The LiveLED 12, by SV, is a LED – RGB color-changing, yoke mounted luminaire for indoor and outdoor venues and applications. The LiveLED 12 features an integrated off board power supply with DMX512 control system.

Smooth RGB color mixing and full range dimming allow for 16.7 million colors and a variety of effects including variable speed cross fades, variable speed color changes, strobes and more. The unit may be operated with DMX controllers, in master / slave synchronization, with other units (with or without a controller), and in stand-alone mode with 49 pre-programmed effects.

ORDERING INFORMATION

MODEL
LLED12

FIXTURE OPTIONS

- 3 Fixtures
- 6 Fixtures
- 9 Fixtures
- 12 Fixtures

FEATURE OPTIONS

- Y Yoke Mount
- F Flange Mount

ACCESSORIES

- Power Control Cable
- Controller Power Supply

Ordering Example: **LLED12-6-Y**

Specifications

Construction

Cast, machined and powder coated aluminum housing with integrated heat sink, formed and powder coated CRS yoke, gasket sealed available for damp locations. This unit is also available for flush mount downlight with flange instead of yoke.

This unit is also available for flush mount downlight with flange instead of yoke.

Lumen Output: 230 lumens

Voltage: 12VDC MAX

Control System

DMX 512 with master/slave or active control via standard XLR connectors (3 pin standard, 5 pin available upon request)

Driver:

Proprietary LED driver technology, driving 7 LED's (3 red, 2 green, 2 royal blue)

Weight: 1 lb. (0.45 kg)

Dimensions: 1.7" L x 2.5" W x 3.0" H

Location Listing: Damp or Dry

Environmental Temperature: -30°F to 140°F

Installation: Any Orientation

Warranty: 2 years