

### Specifications

**Core:** Multi-Strand PMMA Fiber  
**Outer Jacket:** Treated PVC tube  
**Spool Length:** 100 ft. and 200 ft  
**Bend Radius:** Minimum 6x fiber diameter  
**Acceptance Angle:** 75°  
**Numeric Aperture:** 0.60  
**Attenuation:** Less than 1.6% per foot  
**Operating Temperature Range:**  
 Minimum 5°F (-15°C)  
 Maximum 248°F (120°C)



Catalog No.	Number of Fibers	Outer Diameter (mm)
MSE04	4	3.2
MSE07	7	3.8
MSE12	12	5.5
MSE25	25	6.4
MSE50	50	7.9
MSE75	75	9.6
MSE84	84	11.0
MSE100	100	12.0
MSE150	150	15.1

The multi-strand end light is multiple strands of PMMA 0.75mm diameter fiber, covered with a PVC outer sleeving. The PVC is treated with fungicides and UV inhibitors for weather resistance.

Special effects can be achieved by choosing 1 of 2 wheel types – color for a kaleidoscope effect or clear sparkle to create a twinkling effect.

It is available in 100 and 200 continuous feet.

### Applications

- Ceilings
- Architectural Features
- Pool and Spa
- Waterfalls
- Water Features
- Landscape Fixtures

